



LANDLOK® 407 is a flexible, open weave, degradable erosion control blanket produced by Propex and will meet the following Typical Values when tested in accordance with the methods listed below. **Landlok 407** is made from perpendicular rows of photodegradable polypropylene spun and tape yarns woven into a dimensionally stable matrix. The geotextile is designed to hold seed and soil in place, protect emerging seedlings and accelerate vegetation growth in low to moderate erosion applications. This product is NTPEP approved for AASHTO standards.

TYPICAL¹

PROPERTY	TEST METHOD	ENGLISH	METRIC
PHYSICAL			
Mass/Unit Area	ASTM D-6475	2.2 oz/yd ²	75 g/m ²
MECHANICAL			
Tensile Strength (Grab)	ASTM D-6818	460 x 250 lb/ft	6.7 x 3.7 kN/m
Elongation	ASTM D-6818	30 x 40%	30 x 40%
ENDURANCE			
Functional Longevity	Observed	Up to 12 months	Up to 12 months
ROLL SIZES		12.5 ft x 432 ft	3.81 m x 131.7 m
ROLL WEIGHTS		Approx. 83 lbs	Approx. 38 kg

NOTES:

- The property values listed above are effective 08/2006 and are subject to change without notice. A TYPICAL value is the average value obtained when testing the product.



TESTED. PROVEN. TRUSTED
www.geotextile.com

Propex Operating Company, LLC · 6025 Lee Highway, Suite 425 · PO Box 22788 · Chattanooga, TN 37422
ph 423 899 0444 · ph 800 621 1273 · fax 423 899 7619

Geotex®, Landlok®, Pyramat®, X3®, SuperGro®, Petromat® and Petrotac® are registered trademarks of Propex Operating Company, LLC.

This publication should not be construed as engineering advice. While information contained in this publication is accurate to the best of our knowledge, Propex does not warrant its accuracy or completeness. The ultimate customer and user of the products should assume sole responsibility for the final determination of the suitability of the information and the products for the contemplated and actual use. The only warranty made by Propex for its products is set forth in our product data sheets for the product, or such other written warranty as may be agreed by Propex and individual customers. Propex specifically disclaims all other warranties, express or implied, including without limitation, warranties of merchantability or fitness for a particular purpose, or arising from provision of samples, a course of dealing or usage of trade.